



Parker Hannifin Corporation  
Industrial Hose Division  
30242 Lakeland Boulevard  
Wickliffe, OH 44092-1747  
Telephone: (440) 833-2120  
Fax: (440) 833-2230  
www.safehose.com

## PRODUCT UPDATE

### **Series 7541 & 7542 GULLY WASHER<sup>®</sup> Lay Flat PVC Hose** *Selected Updates to Performance, Materials and Dimensional Data*




Series 7541 standard duty and 7542 medium duty lay flat PVC hoses now have performance, dimensional and materials changes. These changes apply ONLY to part numbers with branding shown on the next page. Current inventories will be depleted prior to shipping new inventory on a part-number-by-part-number basis. There are no changes to current part numbers or pricing due to these product updates.

*(Continued on page 2)*

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Wickliffe, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA





Parker Hannifin Corporation  
Industrial Hose Division

## Series 7541 & 7542 GULLY WASHER<sup>®</sup> Lay Flat PVC Hose

### *Selected Updates to Performance, Materials and Dimensional Data*



- Tube:** Black PVC (not oil resistant)
- Temp. Range:** -5°F to + 170°F (-20°C to +76°C)
- Brand Method:** White ink
- Brand Example:** 7541: PARKER SERIES 7541 GULLY WASHER 1-1/2" ID 70 PSI WP KOREA
- Brand Example:** 7542: PARKER SERIES 7542 GULLY WASHER 1-1/2" ID 150 PSI WP FLAME RESISTANT US MSHA IC-257/0 KOREA
- Industry Standards:** MSHA (7542 only)

Part Number	ID (in)	Wall Thickness (in)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	NEW DATA		Std Pack Qty (ft)	Stock Status **	PREVIOUS DATA				
					△ Max Rec WP (psi) @ 68°F	△ Max Rec WP (bar) @ 20°C			Wall Thickness (in)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	△ Max Rec WP (psi) @ 68°F	△ Max Rec WP (bar) @ 20°C
7541-1501	1-1/2	0.055	0.14	0.06	70	4.8	300	Y	0.051	0.13	0.06	80	5.5
7541-2001	2	0.055	0.18	0.08	70	4.8	300	Y	0.051	0.16	0.07	80	5.5
7541-2501	2-1/2	0.059	0.24	0.11	60	4.1	300	Y	0.051	0.21	0.10	65	4.5
7541-3001	3	0.059	0.30	0.14	60	4.1	300	Y	0.053	0.24	0.11	60	4.1
7541-4001	4	0.059	0.36	0.16	60	4.1	300	Y	0.060	0.36	0.16	45	3.1
7541-6001	6	0.071	0.71	0.32	45	3.1	300	Y	0.065	0.63	0.29	40	2.8
7541-8001	8	0.083	1.28	0.58	45	3.1	300	Y	0.070	1.10	0.50	40	2.8
7542-1501	1-1/2	0.075	0.23	0.10	150	10.3	300	Y	0.079	0.20	0.09	150	10.3
7542-2001	2	0.079	0.30	0.14	150	10.3	300	Y	0.083	0.30	0.14	150	10.3
7542-2501	2-1/2	0.083	0.37	0.17	150	10.3	300	Y	0.091	0.40	0.18	150	10.3
7542-3001	3	0.091	0.46	0.21	150	10.3	300	Y	0.091	0.52	0.24	150	10.3
7542-4001	4	0.098	0.66	0.30	140	9.7	300	Y	0.102	0.74	0.34	150	10.3
7542-6001	6	0.106	1.02	0.46	100	6.9	300	Y	0.114	1.25	0.57	120	8.3
7542-8001	8	0.118	1.51	0.68	80	5.5	300	Y	0.120	1.89	0.86	100	6.9

\*\* Stock: "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

△ Working pressures are at +68°F (+20°C). Higher temperatures reduce the available working pressure.