



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747
Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com

PRODUCT UPDATE

Series 7335 High Pressure Jetting Hose – Obsolete

Refer to Series SS122 Lightweight High Pressure Jetting Hose



Series 7335 high pressure jetting hose will be obsolete when inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series SS122 as a suggested replacement.

Please refer to the comparison table on page 2.

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA



(Continued on page 2)



Series 7335 High Pressure Jetting Hose – Obsolete
Refer to Series SS122 Lightweight High Pressure Jetting Hose

	<u>Series SS122</u>	<u>Series 7355</u>
Tube:	Black SBR	Black SBR
Reinforcement:	Multiple textile plies	Multiple textile braids
Cover:	Black SBR; wrapped finish	Black SBR; wrapped finish
Temp Range:	-40°F to +180°F (-40°C to +82°C)	-40°F to +180°F (-40°C to +82°C)
Size Range:	1-1/4" to 4"	1-1/4" to 4"
Design Factor:	4:1	4:1
Packaging:	Coils	Coils
Brand Method:	Black text on blue stripe	Black text on blue stripe
Brand Example:	PARKER SS122 HIGH PRESSURE JETTING HOSE XXX PSI WP MADE IN USA	
Applications:	<ul style="list-style-type: none"> • Slurries, water • Cleaning, stripping, washdown • Construction, general industrial, oil field, shipyards 	

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)	Stock Status **
SS122-1250	1-1/4	31.8	2	1.688	42.9	0.49	0.22	500	34.5	*	100	Y
SS122-1500	1-1/2	38.1	2	1.938	49.2	0.60	0.27	500	34.5	*	100	Y
SS122-2000	2	50.8	2	2.500	63.5	0.96	0.44	500	34.5	*	100	Y
SS122-2500	2-1/2	63.5	2	3.000	76.2	1.15	0.52	500	34.5	*	100	Y
SS122-3000	3	76.2	2	3.500	88.9	1.36	0.62	500	34.5	*	100	N
SS122-4000	4	101.6	2	4.500	114.3	1.75	0.79	300	20.7	*	100	Y
7335-1250	1-1/4	31.8	2	1.750	44.0	0.58	0.26	500	34.5	*	100	n/a
7335-1500	1-1/2	38.1	2	2.008	51.0	0.68	0.31	500	34.5	*	100	n/a
7335-2000	2	50.8	4	2.637	67.0	1.11	0.50	500	34.5	*	100	n/a
7335-2500	2-1/2	63.5	4	3.165	80.4	1.43	0.65	500	34.5	*	100	n/a
7335-3000	3	76.2	4	3.736	94.9	1.83	0.83	500	34.5	*	100	n/a
7335-4000	4	101.6	6	4.898	124.4	2.90	1.32	500	34.5	*	100	n/a

* **Couplings:** Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

** **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.