



Parker Hannifin Corporation  
Industrial Hose Division  
30242 Lakeland Boulevard  
Wickliffe, OH 44092-1747  
Telephone: (440) 833-2120  
Fax: (440) 833-2230  
www.safehose.com

## PRODUCT UPDATE

**Series SS254 Lightweight Petroleum Discharge Hose - Obsolete**  
*Refer to Series SS107/SS107R or  
Series ES145 Petroleum Discharge Hose*



Series SS254 lightweight petroleum discharge hose will be obsolete when inventory is depleted. The discontinuation applies to both standard and non-standard part numbers within the product line, and all quotations will be expired with the discontinuation. Parker continues to offer Series SS107 (black), SS107R (red) and ES145 as suggested replacements.

*Please refer to the comparison table on page 2.*

Series SS107



Series ES145



If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Wickliffe, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA

*(Continued on page 2)*



**Series SS254 Lightweight Petroleum Discharge Hose - Obsolete**  
*Refer to Series SS107/SS107R or  
Series ES145 Petroleum Discharge Hose*

	<b>Series SS107 (black) or SS107R (red)</b>	<b>Series ES145 (Custom Made Hose)</b>
<b>Tube:</b>	Black nitrile	Black nitrile
<b>Reinforcement:</b>	Multiple textile plies with static wire	Multiple textile plies with static wire
<b>Cover:</b>	Black nitrile or red chloroprene; wrapped finish	Black nitrile; wrapped finish
<b>Temp Range:</b>	-40°F to +200°F (-40°C to +93°C)	-40°F to +180°F (-40°C to +82°C)
<b>Size Range:</b>	1-1/4" to 6"	1-1/2" to 6"
<b>Design Factor:</b>	4:1	4:1
<b>Packaging:</b>	Coils	Coils
<b>Applications:</b>	<ul style="list-style-type: none"> <li>• Biodiesel (to B100 in dedicated service), diesel, ethanol, gasoline, oil</li> <li>• In-plant and storage tank transfer/discharge</li> <li>• Delivery/transfer discharge</li> </ul>	

**Series SS254**

<b>Tube:</b>	Black nitrile
<b>Reinforcement:</b>	Multiple textile plies with static wire
<b>Cover:</b>	Black nitrile; wrapped finish
<b>Temp Range:</b>	-40°F to +180°F (-40°C to +82°C)
<b>Size Range:</b>	6" and 8"
<b>Design Factor:</b>	4:1
<b>Packaging:</b>	Coils

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)	Stock Status **
SS107-6000	6	152.4	4	6.670	169.4	3.39	1.54	200	13.8	*	100	N
SS107R-6000	6	152.4	4	6.670	169.4	3.39	1.54	200	13.8	*	100	N
ES145-6000	6	152.4	4	7.063	179.4	5.64	2.56	300	21.0	*	100	N
SS254-6000	6	152.4	4	6.844	173.8	4.25	1.93	150	10.3	*	100	n/a
SS254-8000	8	203.2	4	8.844	224.6	5.74	2.60	150	10.3	*	100	n/a

\* **Couplings:** Refer to CrimpSource at [www.safehose.com](http://www.safehose.com) for coupling recommendations and crimp specifications.

\*\* **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

**WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.