



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747
Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com

PRODUCT UPDATE

Series 7777 GOLD LABEL[®] Jac-Riser Aircraft Fueling Hose EI/API 1529:2005, Type E, Grade 2

Part Number and Length Pattern/Stock Status Update



To be more sensitive to inventory requirements of Select Aircraft Fueling Hose Assembly Fabricators, Parker is updating the length patterns of stocked Series 7777 Jac-Riser hose. Effective immediately, inventoried sizes of Series 7777 will be stocked only in 60-foot lengths; new part numbers for this length are shown in the table on the next page. There are no changes to dimensions or performance due to the length pattern/part number update.

Many jac-riser hose applications require hose lengths of 10, 15, 20 or 30 feet; stocking the hose in 60-foot lengths provides the most efficient use of distributor inventory by maximizing versatility and minimizing the risk of scrap. Stocking the hose in 60-foot lengths also promotes rapid turnover of distributor inventory within the industry-prescribed eight quarters from date of manufacture. All sizes of Series 7777 continue to be available in 100-foot and 200-foot lengths under the part numbers listed on the next page, but will require quoted pricing, minimum order quantities and delivery. Contact Parker.

(Continued on page 2)

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA

800.242.HOSE (4673)
South Gate, CA
Western USA





Series 7777 GOLD LABEL[®] Jac-Riser Aircraft Fueling Hose
EI/API 1529:2005, Type E, Grade 2
Part Number and Length Pattern/Stock Status Update

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **	Min Order Qty (ft)
NEW PART NUMBERS														
77771500-720	1-1/2	38.1	4	2.236	56.8	1.33	0.60	6.0	152.4	300	20.7	60	N	300
77772000-720	2	50.8	4	2.720	69.1	1.61	0.73	8.0	203.2	300	20.7	60	Y	60
77772500-720	2-1/2	63.5	4	3.290	83.6	2.29	1.04	10.0	254.0	300	20.7	60	N	300
77773000-720	3	76.2	4	3.930	99.8	3.15	1.43	12.0	304.8	300	20.7	60	Y	60
77774000-720	4	101.6	4	4.980	126.5	4.44	2.01	16.0	406.4	300	20.7	60	Y	60
NON-STOCK PART NUMBERS														
7777-1500	1-1/2	38.1	4	2.236	56.8	1.33	0.60	6.0	152.4	300	20.7	100	N	500
7777-2000	2	50.8	4	2.720	69.1	1.61	0.73	8.0	203.2	300	20.7	100	N	500
7777-2500	2-1/2	63.5	4	3.290	83.6	2.29	1.04	10.0	254.0	300	20.7	100	N	500
7777-3000	3	76.2	4	3.930	99.8	3.15	1.43	12.0	304.8	300	20.7	100	N	500
7777-4000	4	101.6	4	4.980	126.5	4.44	2.01	16.0	406.4	300	20.7	100	N	500
7777-1500200	1-1/2	38.1	4	2.236	56.8	1.33	0.60	6.0	152.4	300	20.7	200	N	200
7777-2000200	2	50.8	4	2.720	69.1	1.61	0.73	8.0	203.2	300	20.7	200	N	200
7777-2500200	2-1/2	63.5	4	3.290	83.6	2.29	1.04	10.0	254.0	300	20.7	200	N	200
7777-3000200	3	76.2	4	3.930	99.8	3.15	1.43	12.0	304.8	300	20.7	200	N	200
7777-4000200	4	101.6	4	4.980	126.5	4.44	2.01	16.0	406.4	300	20.7	200	N	200

* **Couplings:** Refer to CrimpSource at www.safehose.com for coupling recommendations and crimp specifications.

** **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

WARNING! Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.