



Parker Hannifin Corporation  
 Industrial Hose Division  
 30242 Lakeland Boulevard  
 Wickliffe, OH 44092-1747  
 Telephone: (440) 833-2120  
 Fax: (440) 833-2230  
 www.safehose.com

## PRODUCT UPDATE

### Series 7186 Heater Hose

#### Update to Maximum Recommended Working Pressure



Effective immediately, the maximum recommended working pressures for Series 7186 hose have been recalibrated per the table below. The Design Factor is 4:1 at the new pressures.

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Prev Max Rec WP (psi)	Prev Max Rec WP (bar)	New Max Rec WP (psi)	New Max Rec WP (bar)	Perm Cplg Rec *	Std Pack Qty (ft)	Stock Status **
7186-501	1/2	12.7	2	0.781	19.8	0.17	0.08	6.0	152.4	125	8.6	62	4.3	*	500	Y
7186-501050	1/2	12.7	2	0.781	19.8	0.17	0.08	6.0	152.4	125	8.6	62	4.3	*	5 x 50	N
7186-631	5/8	15.9	2	0.906	23.0	0.20	0.09	8.0	203.2	90	6.2	62	4.3	*	500	Y
7186-631050	5/8	15.9	2	0.906	23.0	0.20	0.09	8.0	203.2	90	6.2	62	4.3	*	5 x 50	Y
7186-751	3/4	19.1	2	1.032	26.2	0.24	0.11	9.0	228.6	70	4.8	62	4.3	*	500	Y
7186-751050	3/4	19.1	2	1.032	26.2	0.24	0.11	9.0	228.6	70	4.8	62	4.3	*	5 x 50	N

\* **Couplings:** Refer to CrimpSource at [www.safehose.com](http://www.safehose.com) for coupling recommendations and crimp specifications.

\*\* **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

**WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.

If there are any questions please contact  
 Parker Customer Service toll-free at:

866.810.HOSE (4673)  
 Wickliffe, OH  
 Eastern USA

800.242.HOSE (4673)  
 South Gate, CA  
 Western USA

