



Parker Hannifin Corporation
Industrial Hose Division
30242 Lakeland Boulevard
Wickliffe, OH 44092-1747
Telephone: (440) 833-2120
Fax: (440) 833-2230
www.safehose.com


NEW PRODUCT

Series 7282 FLEX-EVER™ Barrier Gasoline Dispenser Hose *Conventional Replacement for EPA Stage II Vapor Control Systems*



Parker Series 7282 is a new, eco-friendly premium gasoline dispenser hose. The low permeation construction features a high quality nitrile tube backed by a thin, high strength thermoplastic barrier that meets UL/CARB permeation requirements of $<10\text{g}/\text{m}^2/\text{day}$. The hose is designed to dispense or transfer refined fuels such as biodiesel (to B5 in dedicated and non-dedicated service), diesel, ethanol (see note below), gasoline and oil. The hose meets all Underwriters Laboratories/Canada (UL330/ULC) requirements. The hardwall construction incorporates a dual wire helix that reduces meter creep and provides full suction capability, kink resistance and a path to conduct a static electrical charge to ground. The cover is resistant to abrasion, cuts, oil and ozone, and will not mar the finish of a vehicle.

NOTES:

- The  symbol in the brand/layline signifies the hose as a “UL Recognized Component” for UL gasoline dispenser hose assemblies.
- Not UL listed for E85 service.
- Refer to the Safety and Technical section of Catalog 4800 for safety, handling and use information.

(Continued on page 2)

If there are any questions please contact
Parker Customer Service toll-free at:

866.810.HOSE (4673)
Wickliffe, OH
Eastern USA


800.242.HOSE (4673)
South Gate, CA
Western USA





Parker Hannifin Corporation
Industrial Hose Division

Series 7282 FLEX-EVER™ Barrier Gasoline Dispenser Hose Conventional Replacement for EPA Stage II Vapor Control Systems

- Tube:** Black nitrile with THV barrier
- Reinforcement:** Multiple textile braids with dual wire helix
- Cover:** Black CPE; wrapped finish
- Temp Range:** -40°F to +180°F (-40°C to +82°C)
- Brand Method:** White text on orange stripe
- Brand Example:** PARKER SERIES 7282 FLEX-EVER™ ECO LOW PERM HARDWALL GASOLINE DISPENSING HOSE  MH530 MADE IN USA (date code in white ink opposite)
- Design Factor:** 4:1
- Industry Standards:** CARB CP-206; UL330/CAN ULC-S612; NFPA 30A (factory assemblies)
- Applications:**
 - Biodiesel (to B5 in dedicated and non-service), diesel, ethanol (to E10), gasoline, oil
 - Gasoline dispensers and pumps
- Vacuum:** Full
- Compare To:** Veyance Flexsteel Futura Low Perm
- Packaging:** Reels

Part Number	ID (in)	ID (mm)	Reinf Braids	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Perm Cplg Rec *	Nom Std Pack Qty (ft)	Stock Status **
7282-632	5/8	15.9	2	1.031	26.2	0.37	0.17	3.0	76.2	150	10.3	*	500	N
7282-752	3/4	19.1	2	1.172	29.8	0.44	0.20	4.0	101.6	150	10.3	*	500	N
7282-1002	1	25.4	2	1.453	36.9	0.59	0.27	5.0	127.0	150	10.3	*	500	N

Factory Assemblies: Contact Parker Customer Service

* **Couplings:** Bulk gasoline dispenser hose couplings are not sold separately. Refer to CrimpSource at www.safehose.com for other coupling recommendations and crimp specifications.

** **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

⚠ WARNINGS!

- ▶ Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.
- ▶ Do not use Parker gasoline dispenser hose for aircraft fueling applications. Use only API/NFPA qualified hose for aircraft fueling applications.