



Parker Hannifin Corporation  
Industrial Hose Division  
30242 Lakeland Boulevard  
Wickliffe, OH 44092-1747  
Telephone: (440) 833-2120  
Fax: (440) 833-2230  
www.safehose.com

## PRODUCT UPDATE

### **Series 7392E EPDM Water Suction Hose** *Update and Consolidation of 6" I.D.*



Effective with new production, Part Number 7392E-6000 will incorporate an increased maximum recommended working pressure rating—moving from 100 psi to 150 psi—as well as increased flexibility and lighter weight. Inventories of the previous hose construction have been reduced to prepare for this change.

This change allows Parker to streamline the product offering. Consequently, the following catalog part numbers will be discontinued when current inventories are depleted:

- 7392-6000, 7392-600020
- SW500-6000

The discontinuation applies to both standard and non-standard part numbers within the product lines, and all quotations for those items will be expired with the discontinuation.

Please refer to the table on page 2 for a detailed comparison.

*(Continued on page 2)*

If there are any questions please contact  
Parker Customer Service toll-free at:

866.810.HOSE (4673)  
Wickliffe, OH  
Eastern USA

800.242.HOSE (4673)  
South Gate, CA  
Western USA





Parker Hannifin Corporation  
Industrial Hose Division

# Sales Advisory

## Series 7392E EPDM Water Suction Hose Update and Consolidation of 6" I.D.

**Packaging:** 100-ft coils; 20-ft lengths

### Crimp Specifications

For currently qualified crimp specifications including coupling designation, refer to CrimpSource at [www.safehose.com](http://www.safehose.com).  
Refer to the COS-K4 crimper for crimp specs for hose 4" ID and smaller. Refer to the COS-K6 or COS-K10 crimpers for hose IDs larger than 4".

Part Number	ID (in)	ID (mm)	Reinf Plies	OD (in)	OD (mm)	Approx Wt (lbs/ft)	Approx Wt (kgs/ft)	Min Bend Rad (in)	Min Bend Rad (mm)	Max Rec WP (psi)	Max Rec WP (bar)	Std Pack Qty (ft)	Stock Status **
<b>NEW</b>													
7392E-6000	6	152.4	2	6.625	168.3	3.71	1.68	28.0	711.2	150	10.3	100	Y
7392E-600020	6	152.4	2	6.625	168.3	3.71	1.68	28.0	711.2	150	10.3	20	Y
<b>PREVIOUS</b>													
7392E-6000	6	152.4	4	6.570	166.9	4.16	1.89	30.0	762.0	100	6.9	-	N/A
7392-6000	6	152.4	4	6.831	173.5	6.22	2.82	30.0	762.0	100	6.9	-	N/A
7392-600020	6	152.4	4	6.831	173.5	6.22	2.82	30.0	762.0	100	6.9	-	N/A
SW500-6000	6	152.4	2	6.625	168.3	3.71	1.68	28.0	711.2	150	10.3	-	N/A

\*\* **Stock:** "Y" indicates stocked item; "N" indicates non-stocked item. Stock status subject to change. Contact Parker Customer Service.

**⚠ WARNING!** Couplings attached with bands or clamps may reduce the working pressure of the hose assembly to less than the maximum rated working pressure of the hose. Refer to the NAHAD Industrial Hose Assembly Guidelines.